



Product Data Sheet

339-S Grease

Description: **339-S Grease** is a heavy-duty, multi-purpose graphite grease particularly useful in aluminum and copper casting operations. Typically used a lubricant for aluminum permanent mold casting ejector pin and a plunger lubricant for aluminum and copper die casting.

Typical Properties:

NLGI Grade	: 4
Graphite	: 30%
Thickener	: Lithium
Penetration (@77°F)	: 175-205
Dropping Point	: 350°F
Color	: Black
Shelf Life	: 1 year from ship date

Method of Use: **339-S Grease** is not guaranteed to be compatible with other greases- thoroughly remove old grease before using. It can be swabbed on various surfaces that require lubrication. Consistency makes it an ideal working grease for various metallurgical applications.

Precautions: The customary safeguards employed when storing, handling and application should be employed. To prevent contamination, container should be sealed when not in use. Please refer to Material Safety Data Sheet for proper first aid instructions.

Container Size: 35 lb pails or 400 lb drums