



Product Data Sheet

HCFO

Cold Oven Chain Lubricant

Description: *HCFO* is a high quality graphite lubricant formulated with high-purity, finely ground flake graphite for superior penetration of tight tolerances in oven chains.

Typical Properties:	Solids Content	: 11.0%
	Graphite	: 7 micron natural graphite
	Carrier	: Petroleum Distillate
	Flashpoint	: 176°F
	Weight / gallon	: 7.1 lb/gal
	Consistency	: Light Fluid
Shelf Life	: 2 years from manufacture date	

Method of Use: *HCFO* should be thoroughly mixed before use. Lubricant can be brushed or sprayed on chain. Do not dilute. Stir occasionally while using.

Precautions: Oven temperature must be below 150°F before lubricant is applied. All gas burners, pilot lights, and any other source of ignition including smoking materials must be extinguished before application. Exhaust fans must be running and inspection doors and steam dampers must be open before and during lubrication. Ventilation must be continued until all vapors are exhausted. Do not close oven doors after lubrication until oven has been reheated to baking temperatures. Keep container closed tightly when not in use. The customary safeguards employed when storing, handling and applying combustible materials should be employed.

Please refer to Material Safety Data Sheet for proper first aid instructions.

Note: This product is approved only as a non-food contact lubricant for food processing machinery. Please use caution to avoid food contamination.

Container Size: Cases of (4) 1-gallon cans, 5-gallon pails and 55 gallon drums.



ASBURY GRAPHITE MILLS, INC.
405 Old Main Street • PO Box 144 • Asbury, New Jersey 08802
Phone: 908.537.2155 • Fax: 908.537.2908
Sales Manager: Russell Werkheiser russellw@asbury.com rev 6-1-15 www.asbury.com

For over 119 years, providing value with quality,
consistency and reliability in all we do!